





Instructions for Attaching Trellis System with Dual Lock® Fastener

- 1 Unplug AeroGarden. Disconnect *Lamp Cord* from *Lamp Hood* and remove *Lamp Hood* from *Lamp Arm*.
- 2 Place *Lamp Hood* on flat surface (silver/bottom side up) and carefully remove *Grow Bulbs*. **Caution! Grow Bulbs may be hot!**
- 3
 - Remove backing from one Dual Lock strip. Press adhesive side **firmly** on *Lamp Hood*.
 - Repeat with second strip on opposite side of *Lamp Hood*.- 4
 - Adhere third strip **firmly** to the top of a *Trellis Bracket*.
 - Repeat process with last strip and remaining *Bracket*.

IMPORTANT: Do not connect *Trellis Brackets* to *Lamp Hood* at this time. Adhesives must cure for 24 hours to achieve optimal bond strength.

After 24 hours:

- 5 Match up strips on *Trellis Brackets* to those on *Lamp Hood* and press *Brackets* **firmly** on the *Lamp Hood*. You will hear a “click” when *Trellis Bracket* is connected.
- 6 Reassemble your AeroGarden and plug in.

© 2008 AeroGrow International, Inc.
Fasteners are included in Limited Warranty of Trellis System.
Dual Lock® is a registered trademark of 3M Corporation.